

NP-FL SERIES

(Fluorescent Series Plastisol Inks, Non-Phthalate)

104

Features

- Plastisol ink that can express fluorescent Color.
- Various color, easy access to desired fluorescent colors.
- Suitable to multi Purpose, such as Direct Printing, Transfer Printing, etc.
- Gloss appearance.

Application

- For dark fabric, print white ink underbase FL color, because of low concentration of pigment.
- Can be mixed with <NP-SM&SO SERIES>.
- For Flash Cure, 5-10 sec / 392°F(200°C) is recommended, repeat several times if needed.
- Mix <#4900 FF BASE> for increasing elongation, softness and fast fusion. If you mix more than 10%, Tacky, luster, bad opaque may appear.
- Mix <#4702 MATTE AGENT> for Matte appearance.

Remarks

- Stir before printing for convenient use.
- Conduct cure thoroughly to do not loss adhesiveness and fastness.
- Conduct enough test before main printing.
- If needed to mix other product or material, contact AONE for more information.

Eco-Friendly

- Compliant with CPSIA(Pb, Phthalates).
- Meet standard of Eco-passport, adidas A-01.
- AONE's product does not contain six regulated materials, but we do not examine whole product. We recommend to examine every kind of regulated materials and pre-testing for your own use purpose.

Colors

	4311 FL-ORANGE
	4312 FL-RED
	4313 FL-PINK
	4315 FL-MAGENTA
	4316 FL-PURPLE
	4320 FL-YELLOW
	4330 FL-GREEN
	4340 FL-BLUE

Method

- Substrates: 100% cotton, cotton blends, Polyesters.
- Mesh : 50~150 t/in.
- Cure temp: 320°F (160°C), heating more than 60sec.
- Wash-up: mineral spirit, organic solvent.
- Caution: Do not dry clean, bleach or iron the printed area.

Packing & Storage

- Packaging: 22Kgs
- Storage: Avoid strong Acidic compounds and direct sun keep in cool place(64~90°F / 18~32°C).